

Kardol Quality Products
285 S. West Street
Lebanon, Ohio 45036
513-933-8206 Fax: 513-932-6900

MATERIAL SAFETY DATA SHEET
501782, 501783, 501784, 501786 & 501792
Trade Name: **Fiberglass Tape**

Section 1: Composition / Information on Ingredients

| Hazardous Component | CAS # | Weight Percent | Occupational Exposure Limits | | | Vapor PI@ Temp MM Hg |
|---------------------|-----------|----------------|------------------------------|-----------|-------|-------------------------|
| | | | OSHA PEL | ACGIH TLV | Other | |
| | 7631-86-9 | 5.5% | none | none | | |

Section 2: Physical & Chemical Properties

Appearance & Odor: Fibers assembled into rovings, mats, yarns, fabrics, chopped strands.
pH: Neutral
Vapor Pressure (mm Hg.): none
Vapor Density (AIR = 1): not measurable
Evaporation Rate (Butyl Acetate = 1): none
Boiling Point: >1600°F
Melting Point: >1600°F
Freezing Point: None
Solubility in Water: Small
Specific Gravity or Density (H₂O = 1): Glass=2.6
Material VOC:

Section 3: Fire & Explosion Hazard Data

Flash Point: Does not support combustion
Flammability Limits: LEL: NAUEL: N/A
Extinguishing Media: Use that which is applicable to surrounding fire.
Special Fire Fighting: Fire fighters must wear full protective gear including eye protection and self-contained breathing apparatus.
Unusual Fire and Explosion Hazard: Size materials may thermally decompose or burn emitting toxic fumes and smoke including carbon dioxide and carbon monoxide.

Section 4: Reactivity Hazard Data

Stability: Chemically stable
Conditions to Avoid:
Avoid:
Hazardous Decomposition:

Section 5: Health Hazard Data

Inhalation Risks and Symptoms of Exposure: Temporary upper respiratory irritation.

Skin and Eye Contact Health Risks and Symptoms:

| | | | |
|-------------------------------------|------------------------|--------------------------|----------------------------|
| Carcinogenicity: | NTP Carcinogen: | IARC Monographs: | OSHA Regulated: YES |
| Textile or Continuous Fibrous Glass | Not Listed | Not Classifiable-Group 3 | Not Listed |

Medical Conditions Generally Aggravated by Exposure: Inhalation, skin and eye contact. Pre-existing conditions which may be aggravated by mechanical irritants upon inhalation or skin contact.

EMERGENCY FIRST AID PROCEDURE:

Eye Contact: Flush well with running water for at least 15 minutes. Get medical help if irritation persists.

Skin Contact: Cleanse with soap and water. Get medical help if irritation persists.

Inhalation: Remove from exposure. Get medical help if irritation persists.

INGESTION: Unlikely. Consult physician if unusual reaction is noted.

| |
|---|
| Section 6: Control and Protective Measures |
|---|

Respiratory Protection: Use a NIOSH/MSHA approved dust respirator such as 3M model #8710 or #9900 or equivalent.

Ventilation:

Protective Gloves: Yes

Eye Protection: Goggles, safety glasses or face mask.

Other Protective Clothing: Long Sleeves and cap

Work/Hygienic Practices: Bathe with soap and warm water. Wash work clothes separately and rinse washer after use.

Section 7: Precautions for Safe Handling & Use

IN CASE OF SPILL: Vacuum dust deposits.

WASTE DISPOSAL:

Other Precautions:

DOT
Shipping Name:
Liquid Cleaning Compound
N.O.I

HAZARD INDEX
Health: 0
Flammability:
Reactivity: Not reactive

24 HOUR EMERGENCY NUMBER
1-800-424-9300

KEEP OUT OF REACH OF CHILDREN!!!!