

Kardol Quality Products
285 S. West Street
Lebanon, Ohio 45036
513-933-8206 Fax: 513-932-6900

MATERIAL SAFETY DATA SHEET

505510 & 505530

Trade Name: Deep Green Polyester Based Universal Pigment

Section 1: Material Identification

Chemical Name	CAS #	Weight Percent	Occupational Exposure Limits			Vapor PI@ Temp MM Hg
			OSHA PEL	ACGIH TLV	Other	
Pigment Proprietary	N/A	< 9 %	N/E		N/E	
Pigment Proprietary	N/A	< 5 %	N/E		N/E	
Titanium Dioxide	13463-67-7	< 4 %	N/A		N/A	
Polyester Resin	N/A	> 82 %	N/E		N/E	

Section 2: Physical & Chemical Properties

Boiling Point:	N/A
Vapor Density:	N/A
Evaporation:	N/A
Vapor Pressure:	N/A
Specific Gravity:	1.2
Appearance & Odor:	Green Thick Syrup / Characteristic
Solubility in Water:	Very Slight

Section 3: Fire & Explosion Hazard Data

Flash Point:	N/A
PH:	
Flammability Limits:	UEL N/A, LEL N/A
Extinguisher Media:	CO2, Foam, or Dry Chemical
Special Fire Fighting:	May emit toxic fumes under fire conditions; use NIOSH approved self contained breathing apparatus with full face piece
Unusual Fire Hazard:	Empty containers may contain fumes, cool with water

Section 4: Reactivity Hazard Data

Stability:	Stable, will not undergo hazardous polymerization
Conditions to Avoid:	
Avoid:	Avoid contact with strong acids, bases, or other reactive chemicals
Hazardous Decomposition:	Carbon monoxide, carbon dioxide, various hydrocarbons

Section 5: Health Hazard Data

Inhalation Risks and Symptoms of Exposure: Non hazardous product; Avoid eye and skin exposure do not ingest.